

Scissor Lift

Used Scissor Lift North Dakota - The industrial equipment that utilizes crisscrossed steel linked arms is scissor lifts. Scissor lifts create an “X” support network to facilitate vertical lifting. There is a rectangular platform that is attached to the top of the scissor lift. To maintain operator safety, there are support railings at the top of the platform. The scissor lift has a low profile to maintain stability on hard, compact surfaces like concrete. These units can run on either a combustion engine or electric engine to handle the lifting and transporting of the machine. The scissor lift operates on a vertical plane and if the operator needs to move the lift horizontally, they have to reposition the machine. The lifting components of both regular lift models and rough terrain units rely on the same lifting technology. Rough terrain scissor lifts are adapted for travelling on uneven locations. Higher ground clearance and oversized all-terrain tires enable these machines to travel to tricky locations. Some scissor lifts have 4WD to travel through difficult and muddy locations. Thanks to the higher center of gravity lower lifting heights are available. If you have never operated one before, scissor lifts can seem strange or intimidating. Even though images of scissor lifts moving with the wind are easy to imagine, know that they have been specifically designed to provide complete operator safety and you won't even feel the unit moving as it ascends or while it is extended. A variety of safety tests have to be completed before this unit can be sold. Of course, if you are new to this kind of equipment, it is normal to feel unsure until you familiarize yourself with the unit. It is essential to maintain safety precautions all of the time. Depending on the application, there are a variety of electric scissor lift models to pick from. The model you will prefer will largely depend on the types of jobs you plan on completing. Key factors to consider include how high you will need to reach and the types of loads you will be moving. Extreme heights can be attained by different models depending on your specific application. Smaller models are commonly used for interior applications including warehouses and freight or factory settings. If you do not need the highest capacity model, there is no need to choose the largest unit available. There are extra platforms and railings available to provide additional safety measures. These units are safe and reliable. Many safety inspections and specifications need to be maintained in order for these industrial machines to be available for sale. Scissor lifts help people accomplish tasks that are otherwise unattainable, unreachable or inaccessible. These machines are situated in place before elevating vertically. Before the lift is engaged, the operator will properly position the unit. Numerous safety features have been designed into the machine. Following operational guidelines is essential for everyone's safety. The scissor lift's safety basket creates a secure work area compared to trying to accomplish similar tasks from a ladder or scaffolding. The majority of scissor lifts utilize batteries that are internally mounted inside of the base of the lift to generate power. Electric scissor lifts need to be charged regularly; especially after prolonged work shifts. Many operations charge their equipment daily or change batteries every twelve hours. To charge the scissor lift, the operator parks it close to an electrical outlet within a well-ventilated location. The emergency shut-off switch is engaged upon parking to prevent other operators from driving off while plugged in. The large red button found inside the lift or the basket, close to the charger or the control box is the emergency shut-off switch. Oftentimes, the battery charger is found on the right side of the lift on the base of the machine. Older scissor lifts may have a battery charger found on the back of the unit. The charger is plugged into the AC extension cord in an area that is well-ventilated and then the extension cord is plugged into an electrical outlet. The length of the electrical cord on the battery charger needs to be short to prevent damage or running over it. If the extension cord came out of the battery charger storage location during operation, there is a great potential for extreme danger. Once the scissor lift is plugged in, all of the lights on the charger should ideally become illuminated. Once the unit is plugged in, the batteries automatically start to charge. Once the unit is charged, the battery lights will turn green and the charger will turn off. Models that are older and rely on a meter will show zero volts after they are charged fully and then the charger will also turn off automatically. The machine is ready

to tackle another shift once the batteries are fully charged. It is common for warehouses and certain businesses to keep batteries charging around the clock to allow the scissor lift to operate 24 hours a day.